
Connecting and Disconnecting Devices

<https://campus.barracuda.com/doc/11796847/>

You must log in to your Barracuda Networks product web interface directly to connect or disconnect it to/from the Barracuda Control Server.

Connect a Device

To connect a product to the Barracuda Control Server, log into the web interface as the Barracuda Control Server Account Admin, and go to the **BASIC > Connect Devices** page. Follow the steps on this page to connect the product. For additional information, refer to [Step 5: How to Connect Barracuda Networks Devices to the Barracuda Control Server](#).

Disconnect a Device

To disconnect a product from the Barracuda Control Server, log into your Barracuda Networks product web interface. Go to the **ADVANCED > Cloud Control** page, click *No* for **Connect to Barracuda Cloud Control**, and click **Save**. Go to the **BASIC > Dashboard** page of your product, and verify that the **Cloud Control** status displays as *Not Connected*. When you log into the Barracuda Control Server, the product no longer displays in the [product tree](#).

© Barracuda Networks Inc., 2024 The information contained within this document is confidential and proprietary to Barracuda Networks Inc. No portion of this document may be copied, distributed, publicized or used for other than internal documentary purposes without the written consent of an official representative of Barracuda Networks Inc. All specifications are subject to change without notice. Barracuda Networks Inc. assumes no responsibility for any inaccuracies in this document. Barracuda Networks Inc. reserves the right to change, modify, transfer, or otherwise revise this publication without notice.