

Multiple Network Adapters on Real Servers

<https://campus.barracuda.com/doc/3538973/>

Real Servers that are on multiple networks simultaneously may break the route path. If a Real Server has more than one network adapter enabled, which gives traffic an alternate route around the Barracuda Load Balancer, the deployment will not work properly even though it may appear to work initially. There are two exceptions where Real Servers may have multiple network adapters:

- The networks that the Real Servers are on are isolated from each other and cannot access the WAN network without going through the Barracuda Load Balancer.
- Static routes for incoming and outgoing traffic for each IP address of each Real Server have been defined.

Related Articles

- [Direct Server Return Deployment](#)
- [Deploying in a Linux Environment](#)
- [Deploying in a Windows/XP Environment](#)
- [Deployment in a Microsoft Windows Server 2003, 2008, and 2012 Environment](#)

© Barracuda Networks Inc., 2024 The information contained within this document is confidential and proprietary to Barracuda Networks Inc. No portion of this document may be copied, distributed, publicized or used for other than internal documentary purposes without the written consent of an official representative of Barracuda Networks Inc. All specifications are subject to change without notice. Barracuda Networks Inc. assumes no responsibility for any inaccuracies in this document. Barracuda Networks Inc. reserves the right to change, modify, transfer, or otherwise revise this publication without notice.