

---

## Voice over IP

<https://campus.barracuda.com/doc/43847026/>

VoIP has become the standard for voice communication over IP networks. VoIP allows voice and data traffic to be processed on a single network making more efficient use of the already existing infrastructure. Currently the Barracuda NG Firewall supports three different types of Voice over Internet Protocols (VoIP).

- [SIP](#)
- [SCCP](#)
- [H.323 Neighbor Gatekeeper](#)

### SIP

---

SIP is the most widely used VoIP Protocol. Use the SIP proxy on the Barracuda NG Firewall to enable VoIP transmissions through the firewall. The legacy SIP firewall plugin is also included, but Barracuda Networks recommends using the newer SIP proxy.

For more information, see [SIP Proxy](#) or [How to Configure the SIP Plugin Module](#).

### SCCP (Skinny)

---

SCCP is a proprietary VoIP standard now owned by Cisco Networks. SCCP uses a SKINNY signaling connection and dynamic RTP connection for data transmission (audio, video, ...).

For more information, see [How to Configure VoIP Connections with the Skinny \(SCCP\) Firewall Plugin](#).

### H.323

---

H.323 is a protocol that defines communication (audio and video) in any IP based network. The Barracuda NG Firewall acts as a H.323 neighbor gatekeeper.

For more information, see [How to Configure the H.323 Neighbor Gatekeeper](#).

© Barracuda Networks Inc., 2020 The information contained within this document is confidential and proprietary to Barracuda Networks Inc. No portion of this document may be copied, distributed, publicized or used for other than internal documentary purposes without the written consent of an official representative of Barracuda Networks Inc. All specifications are subject to change without notice. Barracuda Networks Inc. assumes no responsibility for any inaccuracies in this document. Barracuda Networks Inc. reserves the right to change, modify, transfer, or otherwise revise this publication without notice.