Barracuda ArchiveOne

How to Change the Offline Archive Directory for Laptop Client Users

https://campus.barracuda.com/doc/46207937/

Use the steps in this article to change the directory where the pseudo-repositories are created for offline directories.

Before Getting Started

1. In Notepad, open the file **\\[configuration_server]\Add-ins\AOnePol\Repositories\[Pseudo_Directory_Name].c2c**
   where **[configuration_server]** is the name of the server hosting the Add-ins shared folder and **[Pseudo_Directory_Name]** is the name of the offline archive you wish to change.
2. Locate the line **DirForTemp=**
3. Update the line to point to the new folder path: **DirForTemp=[path]**
   where **[path]** is the new folder path you want to use.
4. Save and close the file.
5. Type `services.msc` in the **Start Search** box, and press **Enter**.
6. In the **Services** window, right-click **Archive One Service**, and click **Restart**.
7. In the ArchiveOne admin console, right-click the Status Node, and click **Configure**.
8. Click the **Offline Archive** tab, and click **Synchronise now**.

Change the Directory

1. In Notepad, open the file **\\[configuration_server]\Add-ins\AOnePol\AOneConfig.C2C**
   where **[configuration_server]** is the name of the server hosting the Add-ins shared folder.
2. Add the following new line to the file: **PseudoTempPathOverride=[path]**
   where **[path]** is the new folder path you want to use.
3. Save and close the file.
4. Type `services.msc` in the **Start Search** box, and press **Enter**.
5. In the **Services** window, right-click **Archive One Service**, and click **Restart**.
6. In the ArchiveOne admin console, right-click the **Status** node, and click **Configure**.
7. Click the **Offline Archive** tab, and click **Synchronise now** to create the offline archives in the new location.