

Understanding the Unarchive Process

<https://campus.barracuda.com/doc/46208596/>

- Unarchiving can only be performed against an entire, specific mailbox or a named folder in a specific mailbox.
- Unarchiving activity only occurs in the first phase; there is no activity in the second phase.
- Messages are unarchived to the message stub location; for example, if you have moved a stub from the **Inbox** to a new folder named **Important**, unarchived messages are placed in the **Important** folder.
- If a message stub is deleted, the message cannot be unarchived.
- You cannot unarchive messages back into a PST file.
- The unarchive process does not unarchive messages back into a PST; for example, if you have archived a PST file and have not finalized the PST, the messages are not unarchived.
- Unarchiving does not delete the archived data in the repository; a copy of the message is written back to the user's mailbox and the archived item remains in the repository. Therefore, you can still run archive searches from the ArchiveOne Admin console for this data.
- Rate control has no effect on the unarchive process.

© Barracuda Networks Inc., 2024 The information contained within this document is confidential and proprietary to Barracuda Networks Inc. No portion of this document may be copied, distributed, publicized or used for other than internal documentary purposes without the written consent of an official representative of Barracuda Networks Inc. All specifications are subject to change without notice. Barracuda Networks Inc. assumes no responsibility for any inaccuracies in this document. Barracuda Networks Inc. reserves the right to change, modify, transfer, or otherwise revise this publication without notice.