

How to Configure LDAP Authentication for macOS Directory Services












<https://campus.barracuda.com/doc/48202784/>

To retrieve authentication information from a macOS Directory server, configure it as an external LDAP authentication server.


Configure LDAP authentication for macOS directory services

1. Go to **CONFIGURATION > Configuration Tree > Box > Infrastructure Services > Authentication Service**
2. In the left menu, select **LDAP Authentication**.
3. Click **Lock**.
4. Enable LDAP as external directory service.
5. In the **Basic** table, add a new entry for each Base DN. Configure the following settings:
 - **LDAP Base DN** - Enter the distinguished name for the user organizational unit.
 - **LDAP Server / Port** - Enter the IP address and port for the macOS Directory server (default: port 389).
 - **Anonymous** - Select **No**.
 - **LDAP Admin DN / Password** - Name and password of the administrator authorized to perform LDAP queries.
 - **Group Attribute** - Enter gidNumber.
 - **Cache LDAP Groups** - Enable checkbox to display groups by name.
 - **Logon to Authenticate** - Enable checkbox.



Basic

LDAP Base DN	<input checked="" type="checkbox"/>	<input type="text" value="dc=example,dc=doc"/>	
LDAP Server	<input checked="" type="checkbox"/>	<input type="text" value="10.0.10.40"/>	
LDAP Server Port		<input type="text" value="389"/>	
LDAP User Field		<input type="text" value="uid"/>	
LDAP Password Field		<input type="text" value="userPassword"/>	
Anonymous		<input type="text" value="No"/>	
LDAP Admin DN	<input checked="" type="checkbox"/>	<input type="text" value="uid=diradm,cn=users,dc=example,dc=doc"/>	
LDAP Admin Password	<input checked="" type="checkbox"/>	<input type="text" value="Current"/> <input type="text" value="New"/> <input type="text" value="Confirm"/> <input type="text" value="Strength"/>	
Group Attribute	<input checked="" type="checkbox"/>	<input type="text" value="gidNumber"/>	
Cache LDAP Groups	<input checked="" type="checkbox"/>	<input type="text" value="Yes"/>	
Offline Sync [m]		<input type="text" value="60"/>	

Mail Lookup

Additional Mail Fields	<input type="text"/>	
------------------------	----------------------	---

Extended

Use SSL	<input type="checkbox"/>	
Logon to Authenticate	<input checked="" type="checkbox"/>	

6. Click **OK**.
7. Click **Send Changes** and **Activate**.

You can now retrieve authentication information from your macOS Directory server.

Figures

1. 62_ldap.png

© Barracuda Networks Inc., 2019 The information contained within this document is confidential and proprietary to Barracuda Networks Inc. No portion of this document may be copied, distributed, publicized or used for other than internal documentary purposes without the written consent of an official representative of Barracuda Networks Inc. All specifications are subject to change without notice. Barracuda Networks Inc. assumes no responsibility for any inaccuracies in this document. Barracuda Networks Inc. reserves the right to change, modify, transfer, or otherwise revise this publication without notice.