

How to Configure Network-Based Repositories

<https://campus.barracuda.com/doc/48660835/>

This article refers to the Barracuda ArchiveOne for Files version 7.2.0 and higher.

See [Repositories Node](#) for additional information.

By default, the ArchiveOne Data Processing Services are installed using the local system account which usually does not have access to network-based resources such as network drives. However, if you wish to host your repositories on a different server than the one running the services, you can configure network-based repositories by completing the following steps:

1. Ensure that no Policies are running in the ArchiveOne For Files Management Console.
2. Open the **Microsoft Services** console. Right-click **ArchiveOne Core Service** and click **Stop**, and then right-click **ArchiveOne Broker Service** and click **Stop**.
3. On the **Properties** for each of the ArchiveOne Data Processing Services, change the **Log On** account from **Local System** to another account with privileges to the network share where you want to host your repositories.
4. Restart **ArchiveOne Core Service** and **ArchiveOne Broker Service**.

The ArchiveOne Data Processing Services are now running under the newly configured service account. You can now create repositories using UNC paths for any network-based repository.

© Barracuda Networks Inc., 2024 The information contained within this document is confidential and proprietary to Barracuda Networks Inc. No portion of this document may be copied, distributed, publicized or used for other than internal documentary purposes without the written consent of an official representative of Barracuda Networks Inc. All specifications are subject to change without notice. Barracuda Networks Inc. assumes no responsibility for any inaccuracies in this document. Barracuda Networks Inc. reserves the right to change, modify, transfer, or otherwise revise this publication without notice.