

How to Configure an SMTP Relay Server to Send Alerts

<https://campus.barracuda.com/doc/75696035/> You can customize the email domain for all emails sourced from the Barracuda Web Security Gateway. If you want your internal mail to be sourced from a specific domain, enter your SMTP relay server in the **SMTP Server** field in the **Email Notifications** section of the **BASIC > Administration** page. See the example below.

The following variables will use this server:

- System Alerts Email Address
- Threat Alerts Email Address
- System Contact Email Address
- Web App Monitor Email Address
- **Policy Alerts Email Address** on the **BLOCK/ACCEPT > Exceptions** page
- Test SMTP connection
- Renewal emails
- Infection Alert (ATP Alert, Virus Alert)
- Reports
- Backup Failure



Email Notifications	
SMTP Server:	<input type="text" value="smtp.gmail.com"/> <i>The mail server you want to use for sending notifications.</i>
SMTP Port:	<input type="text" value="587"/> <i>The notification mail server's SMTP port.</i>
Username:	<input type="text" value="Chu.Max"/>
Password:	<input type="password" value="....."/>

Figures

1. SMTPRelayAlerts.png

© Barracuda Networks Inc., 2024 The information contained within this document is confidential and proprietary to Barracuda Networks Inc. No portion of this document may be copied, distributed, publicized or used for other than internal documentary purposes without the written consent of an official representative of Barracuda Networks Inc. All specifications are subject to change without notice. Barracuda Networks Inc. assumes no responsibility for any inaccuracies in this document. Barracuda Networks Inc. reserves the right to change, modify, transfer, or otherwise revise this publication without notice.