

Adding a Loggly Cloud Syslog Server

<https://campus.barracuda.com/doc/92767440/>

Perform the following steps to add a Loggly Cloud Syslog server:

1. Go to the **ADVANCED > Export Logs** page.
2. In the **Add Export Log Server** window, specify values for the following:
 - **Name** – Enter a name for the Loggly service.
 - **Log Server Type** – Select **CloudSyslog Service**.
 - **IP Address or Hostname** – Enter the IP address or the hostname of the Loggly service.
For example: *logs-01.loggly.com*
 - **Port** – Enter the port associated with the IP address of the Loggly service.
 - **Token** – Enter the token for Loggly service. For
example: *0a7c8023-92a7-4c9c-90f3-2d18453fdafa@41058*, where 41058 is the Loggly ID
that should be mentioned after the token.
 - **Log Timestamp and Hostname** – Set to **Yes** if you want to log the date and time of the
event, and the hostname configured on the **BASIC > IP Configuration > Domain
Configuration** section.
 - **Comment** – (Optional) Enter comment about the new setting.
3. Click **Add**.

© Barracuda Networks Inc., 2024 The information contained within this document is confidential and proprietary to Barracuda Networks Inc. No portion of this document may be copied, distributed, publicized or used for other than internal documentary purposes without the written consent of an official representative of Barracuda Networks Inc. All specifications are subject to change without notice. Barracuda Networks Inc. assumes no responsibility for any inaccuracies in this document. Barracuda Networks Inc. reserves the right to change, modify, transfer, or otherwise revise this publication without notice.