Hardware

https://campus.barracuda.com/doc/96026600/

> If you are deploying your CloudGen Firewall F-Series via Zero Touch Deployment, see How to Deploy a Hardware Firewall with Zero Touch Deployment.

The CloudGen Firewall F-Series hardware appliances ship with a Quick Start Guide. Follow this guide to connect to your firewall. To protect your network, follow the instructions for the standard deployment:

Step 1. (Optional) Install the CloudGen Firewall in a Rack

Some F-Series Firewalls are desktop sized; the larger models can be mounted in standard-sized racks.

For more information, see Rack Installation of Barracuda Networks Appliances.

Step 2. Connect the Firewall to the Network

The management port for the F-Series Firewall differs depending on the model. Connect the management port to the network the management PC is in.

Hardware System	Management Port	WAN Port
F10 - F400	Port 1	Port 4
F600	Port 1	-
F800	MGMT port	-
F900	MGMT port	-

F1000	MGMT port	-

Step 3. Configure the Client

Configure your client PC to use the following static IP address configuration for the network interface connected to the firewall:

- **IP Address** – 192.168.200.100
- **Netmask** – 255.255.255.0
- **Gateway** – 192.168.200.200
- **DNS Servers** – Enter DNS servers in your network, or use public DNS servers.

Step 4. Complete the Quick Start Guide

Every F-Series Firewall is shipped with the [Quick Start Guide](). Complete all the steps listed in the guide for the Standard Deployment Mode.

Next Steps

To start login and configuration of your CloudGen Firewall, see [Get Started]().

Figures

1. hw_deployment_std.png