
File Retries APIs

<https://campus.barracuda.com/doc/96771968/>

This section includes the following topics:

- Input Parameters
- Output Parameters
- Error codes

Input Parameters

fileretries: integer value, allowed values are between 0 (no retries) and 3.

Command example

The following example provides for 2 file retries.

POST <https://<environment>/v2/accounts/<account>/computers/<computer>/settings/apply>

```
{  
  
  "fileretries": 2  
  
}
```

Output Parameters

The output is an id of the operation, which can be used to track completion status via the command below.

Result of the operation

Status can be obtained via the command below The status is either success or error, also providing the reason for the failure.

GET https://<environment>/v2/accounts/<account>/computers/<computer>/action/{id}/status

Error Codes

The reason for the failure can be matched to one of the error codes below:

- Running_Actions_PreventPreferencesUpdate - cannot update preferences while Backups, Restores or Deletes are running
- Running_Actions_FailedToAcquireLock - critical error, failed to acquire lock for the operation (this never happens)

© Barracuda Networks Inc., 2024 The information contained within this document is confidential and proprietary to Barracuda Networks Inc. No portion of this document may be copied, distributed, publicized or used for other than internal documentary purposes without the written consent of an official representative of Barracuda Networks Inc. All specifications are subject to change without notice. Barracuda Networks Inc. assumes no responsibility for any inaccuracies in this document. Barracuda Networks Inc. reserves the right to change, modify, transfer, or otherwise revise this publication without notice.