Connecting to a Registered Hyper-V Host

https://campus.barracuda.com/doc/96772138/

This API can be used to ensure that the provided host id is valid.

This section includes the following topics:

- Input Parameters
- Output Parameters

Input Parameters

The following table provides the parameters and descriptions.

Parameter	Description
id	Integer. Numeric host id, obtained via the Register API call, or after registration via the Get registered hosts API call.
sessionId	String. Containing a GUID, obtained via a call to API Hyper-V Create Host Browsing Session.

Example


```
{
 "id": 2,
  "sessionId": "5d05495f-39e5-4e4e-ad0c-e351cc2c78f3"
}
```


Output Parameters

Boolean (true or false), denoting the result of the operation (true when the host id points to a valid registered hosts, false otherwise)

Error Code

ErrorCode.HostNotInCatalog - if the provided host id integer from Input section does not point to a valid Hyper-V server (the correct ids can be obtained via get list of hosts)

Example POST

POST /v2/accounts/test_acc/computers/0000/restore/hyperv/host/connect

Input Parameters

```
{
   "id": 1,
   "sessionId": "string"
}
```

Output Parameters

Response status: 200 Accepted (for online operation)

Example Response

```
{
  "data": {
    "isConnected":true
```

```
  }
}
```

© Barracuda Networks Inc., 2024 The information contained within this document is confidential and proprietary to Barracuda Networks Inc. No portion of this document may be copied, distributed, publicized or used for other than internal documentary purposes without the written consent of an official representative of Barracuda Networks Inc. All specifications are subject to change without notice. Barracuda Networks Inc. assumes no responsibility for any inaccuracies in this document. Barracuda Networks Inc. reserves the right to change, modify, transfer, or otherwise revise this publication without notice.